

WEGA Plus Single Channel



SKU	Input Power (W) ±3%	Efficacy	Spectrum	Optics	PPF Output (400–700 nm) (μmol/s)	PF Output (400–800 nm) (μmol/s)	PPE (at 100% power) (μmol/J)	PE (at 100% power) (μmol/J)	Input Voltage (V) ±10%	Input Current (A) ±10%
HGC906504-01	760	Standard	R90G5B5	125°	2650	2650	3.5	3.5	230/400	3.3/1.9
HGC906561-01	760	Standard	R90G5B5	150°	2600	2600	3.42	3.42	230/400	3.3/1.9
HGC906564-01	760	Standard	FR5R85G5B5	150°	2470	2600	3.25	3.42	230/400	3.3/1.9
HGC906505-01	760	High Efficiency	R90G5B5	125°	2900	2900	3.8	3.8	230/400	3.3/1.9
HGC906562-01	760	High Efficiency	R90G5B5	150°	2850	2850	3.75	3.75	230/400	3.3/1.9
HGC906565-01	760	Standard	R60G22B18	125°	2400	2400	3.15	3.15	230/400	3.3/1.9

All types	Value
Mains Freq	50/60 Hz
Power Factor	> 0.95
Isolation Class	Class I
IP Rating	IP65
THD	< 15%
Inrush Current	< 25 A
Connector	Wieland RST20i3 GN
Dimensions (L x W x H)	62 x 27 x 12 cm
Weight	13.4 kg
Temperature Ambient	0 – 35 °C
Light Maintenance (L90)	36000 h

Intended use	
Controlled Environment	Indoor, non-stacked greenhouse
Lighting Scheme	Horizontal, Top Light use, Sole source or supplemental
Dimming Communication*	ModBus RTU, Horti Led Protocol (HLP), 0–10V (ANSI C137.1 (9V)), (IEEE1901.1 power inlet)
Dimming Range*	100% – 15%

*with PLC transmitter

© 2025 Gavita International B.V.. All rights reserved. The information contained in this document may be subject to change without prior notice. Gavita International B.V. makes no representation or warranty regarding the accuracy or completeness of the information provided and accepts no liability for any actions taken based on it. This document does not constitute a commercial offer and does not form part of any quotation or contract unless expressly agreed by Gavita International B.V..